

● LEDトンネル照明器具仕様一覧

新設器具200V

No.	用途	器具形式	器具種別	器具光束	調光	入力仕様 [電圧・周波数]	定格 消費電力
1	基本照明	SE20S03003BL-TS-V2	一般形	3,500 1m	-	AC200V ~265V 50/60Hz	32.5 W
2		SE20S03003BL-D-TS-V2	調光形		50%		
3		SE20SP03003BL-TS-V2	電池内蔵一般形		-		36.0 W
4		SE20SP03003BL-D-TS-V2	電池内蔵調光形		50%		
5		SE20S04004BL-TS-V2	一般形	4,650 1m	-		43.5 W
6		SE20S04004BL-D-TS-V2	調光形		50%		
7		SE20SP04004BL-TS-V2	電池内蔵一般形		-		47.0 W
8		SE20SP04004BL-D-TS-V2	電池内蔵調光形		50%		
9		SE20S05005BL-TS-V2	一般形	5,850 1m	-		54.0 W
10		SE20S05005BL-D-TS-V2	調光形		50%		
11		SE20SP05005BL-TS-V2	電池内蔵一般形		-		57.5 W
12		SE20SP05005BL-D-TS-V2	電池内蔵調光形		50%		
13		SE20S06006BL-TS-V2	一般形	7,000 1m	-		65.0 W
14		SE20S06006BL-D-TS-V2	調光形		50%		
15		SE20SP06006BL-TS-V2	電池内蔵一般形		-		71.0 W
16		SE20SP06006BL-D-TS-V2	電池内蔵調光形		50%		
17		SE20S08008BL-TS-V2	一般形	9,350 1m	-		86.5 W
18		SE20S08008BL-D-TS-V2	調光形		50%		
19		SE20SP08008BL-TS-V2	電池内蔵一般形		-		92.5 W
20		SE20SP08008BL-D-TS-V2	電池内蔵調光形		50%		
21	入口照明	SE20S04002B-TS-V2	一般形	6,200 1m	-	AC200V ~265V 50/60Hz	42.5 W
22		SE20S04002B-D-TS-V2	調光形		50%		
23		SE20S06003B-TS-V2	一般形	9,350 1m	-		64.5 W
24		SE20S06003B-D-TS-V2	調光形		50%		
25		SE20S08004B-TS-V2	一般形	12,450 1m	-		84.0 W
26		SE20S08004B-D-TS-V2	調光形		50%		
27		SE20S12006B-TS-V2	一般形	18,750 1m	-		126 W
28		SE20S12006B-D-TS-V2	調光形		50%		
29		SE20S16008B-TS-V2	一般形	25,000 1m	-		167 W
30		SE20S16008B-D-TS-V2	調光形		50%		
31		SE20S20010B-TS-V2	一般形	31,250 1m	-		210 W
32		SE20S20010B-D-TS-V2	調光形		50%		
33		SE20S24012B-TS-V2	一般形	37,550 1m	-		251 W
34		SE20S24012B-D-TS-V2	調光形		50%		
35		SE20S28014B-TS-V2	一般形	43,800 1m	-		294 W
36		SE20S28014B-D-TS-V2	調光形		50%		

● LEDトンネル照明器具仕様一覧

新設器具400V

No.	用途	器具形式	器具種別	器具光束	調光	入力仕様 [電圧・周波数]	定格 消費電力
37	基本照明	SE20S03003BL-TS-V2	一般形	3,500 1m	-	AC415V ~460V 50/60Hz	33.5 W
38		SE20S03003BL-D-TS-V2	調光形		50%		
39		SE20SP03003BL-TS-V2	電池内蔵一般形	3,500 1m	-		37.0 W
40		SE20SP03003BL-D-TS-V2	電池内蔵調光形		50%		
41		SE20S04004BL-TS-V2	一般形	4,650 1m	-		44.5 W
42		SE20S04004BL-D-TS-V2	調光形		50%		
43		SE20SP04004BL-TS-V2	電池内蔵一般形		-		
44		SE20SP04004BL-D-TS-V2	電池内蔵調光形		50%		
45		SE20S05005BL-TS-V2	一般形	5,850 1m	-		55.0 W
46		SE20S05005BL-D-TS-V2	調光形		50%		
47		SE20SP05005BL-TS-V2	電池内蔵一般形		-		
48		SE20SP05005BL-D-TS-V2	電池内蔵調光形		50%		
49		SE20S06006BL-TS-V2	一般形	7,000 1m	-		66.0 W
50		SE20S06006BL-D-TS-V2	調光形		50%		
51		SE20SP06006BL-TS-V2	電池内蔵一般形		-		
52		SE20SP06006BL-D-TS-V2	電池内蔵調光形		50%		
53	SE20S08008BL-TS-V2	一般形	9,350 1m	-	87.5 W		
54	SE20S08008BL-D-TS-V2	調光形		50%			
55	SE20SP08008BL-TS-V2	電池内蔵一般形		-			
56	SE20SP08008BL-D-TS-V2	電池内蔵調光形		50%			
57	入口照明	SE20S04002B-TS-V2	一般形	6,200 1m	-	AC415V ~460V 50/60Hz	45.0 W
58		SE20S04002B-D-TS-V2	調光形		50%		
59		SE20S06003B-TS-V2	一般形	9,350 1m	-		65.0 W
60		SE20S06003B-D-TS-V2	調光形		50%		
61		SE20S08004B-TS-V2	一般形	12,450 1m	-		85.0 W
62		SE20S08004B-D-TS-V2	調光形		50%		
63		SE20S12006B-TS-V2	一般形	18,750 1m	-		129 W
64		SE20S12006B-D-TS-V2	調光形		50%		
65		SE20S16008B-TS-V2	一般形	25,000 1m	-		169 W
66		SE20S16008B-D-TS-V2	調光形		50%		
67		SE20S20010B-TS-V2	一般形	31,250 1m	-		213 W
68		SE20S20010B-D-TS-V2	調光形		50%		
69		SE20S24012B-TS-V2	一般形	37,550 1m	-		254 W
70		SE20S24012B-D-TS-V2	調光形		50%		
71		SE20S28014B-TS-V2	一般形	43,800 1m	-		299 W
72		SE20S28014B-D-TS-V2	調光形		50%		

● LEDトンネル照明器具仕様一覧

内機交換ユニット200V

No.	用途	器具形式	器具種別	器具光束	調光	入力仕様 [電圧・周波数]	定格 消費電力
73	基本照明	LTUSE20S103	一般形	3,100 1m	-	AC200V ~265V 50/60Hz	32.5 W
74		LTUSE20S103D	調光形		50%		
75		LTUSEP20S103	電池内蔵一般形	3,100 1m	-		36.0 W
76		LTUSEP20S103D	電池内蔵調光形		50%		
77		LTUSE20S104	一般形	4,200 1m	-		43.5 W
78		LTUSE20S104D	調光形		50%		
79		LTUSEP20S104	電池内蔵一般形		-		
80		LTUSEP20S104D	電池内蔵調光形		50%		
81		LTUSE20S105	一般形	5,250 1m	-		54.0 W
82		LTUSE20S105D	調光形		50%		
83		LTUSEP20S105	電池内蔵一般形		-		
84		LTUSEP20S105D	電池内蔵調光形		50%		
85		LTUSE20S106	一般形	6,300 1m	-		65.0 W
86		LTUSE20S106D	調光形		50%		
87		LTUSEP20S106	電池内蔵一般形		-		
88		LTUSEP20S106D	電池内蔵調光形		50%		
89	LTUSE20S108	一般形	8,400 1m	-	86.5 W		
90	LTUSE20S108D	調光形		50%			
91	LTUSEP20S108	電池内蔵一般形		-			
92	LTUSEP20S108D	電池内蔵調光形		50%			
93	入口照明	LTUSE20S202	一般形	3,300 1m	-	AC200V ~265V 50/60Hz	42.5 W
94		LTUSE20S202D	調光形		50%		
95		LTUSE20S203	一般形	7,700 1m	-		64.5 W
96		LTUSE20S203D	調光形		50%		
97		LTUSE20S204	一般形	11,000 1m	-		84.0 W
98		LTUSE20S204D	調光形		50%		
99		LTUSE20S206	一般形	16,500 1m	-		126 W
100		LTUSE20S206D	調光形		50%		
101		LTUSE20S208	一般形	22,000 1m	-		167 W
102		LTUSE20S208D	調光形		50%		
103		LTUSE20S2010	一般形	27,500 1m	-		210 W
104		LTUSE20S2010D	調光形		50%		

● LEDトンネル照明器具仕様一覧

内機交換ユニット400V

No.	用途	器具形式	器具種別	器具光束	調光	入力仕様 [電圧・周波数]	定格 消費電力
105	基本照明	LTUSE20S103	一般形	3,100 1m	-	AC415V ~460V 50/60Hz	33.0 W
106		LTUSE20S103D	調光形		50%		
107		LTUSE20S104	一般形	4,200 1m	-		44.0 W
108		LTUSE20S104D	調光形		50%		
109		LTUSE20S105	一般形	5,250 1m	-		55.0 W
110		LTUSE20S105D	調光形		50%		
111		LTUSE20S106	一般形	6,300 1m	-		66.0 W
112		LTUSE20S106D	調光形		50%		
113		LTUSE20S108	一般形	8,400 1m	-		88.0 W
114		LTUSE20S108D	調光形		50%		
115	入口照明	LTUSE20S202	一般形	3,300 1m	-	AC415V ~460V 50/60Hz	45.0 W
116		LTUSE20S202D	調光形		50%		
117		LTUSE20S203	一般形	7,700 1m	-		65.0 W
118		LTUSE20S203D	調光形		50%		
119		LTUSE20S204	一般形	11,000 1m	-		85.0 W
120		LTUSE20S204D	調光形		50%		
121		LTUSE20S206	一般形	16,500 1m	-		129 W
122		LTUSE20S206D	調光形		50%		
123		LTUSE20S208	一般形	22,000 1m	-		169 W
124		LTUSE20S208D	調光形		50%		
125		LTUSE20S2010	一般形	27,500 1m	-		213 W
126		LTUSE20S2010D	調光形		50%		